

3 φ 50Hz 380V

(°C) 54.4  
 (°C) 7.2  
 (°C) 11.1  
 (°C) 8.3

R410A

**CAPACITY (W)**

Condensing Temperature	Evaporating Temperature (°C)							
	-15	-10	-5	0	5	7.2	10	12
35.0	10,150	12,350	14,690	17,150	19,760	20,940	22,490	23,620
40.0	9,250	11,370	13,640	16,060	18,640	19,820	21,370	22,500
45.0	8,410	10,450	12,660	15,030	17,580	18,760	20,300	21,440
50.0	7,650	9,600	11,740	14,070	16,580	17,750	19,280	20,420
54.4		8,910	10,980	13,260	15,740	16,900	18,430	19,560
60.0			10,100	12,310	14,740	15,880	17,400	18,520
65.0				11,530	13,910	15,030	16,530	17,640

**POWER (W)**

Condensing Temperature	Evaporating Temperature (°C)							
	-15	-10	-5	0	5	7.2	10	12
35.0	3,630	3,610	3,620	3,650	3,700	3,740	3,780	3,820
40.0	4,140	4,100	4,080	4,100	4,140	4,170	4,210	4,240
45.0	4,770	4,690	4,640	4,630	4,650	4,670	4,700	4,730
50.0	5,520	5,390	5,300	5,250	5,230	5,240	5,260	5,280
54.4		6,100	5,950	5,860	5,810	5,800	5,800	5,810
60.0			6,890	6,730	6,620	6,600	6,570	6,570
65.0				7,600	7,430	7,380	7,330	7,310

**CURRENT (A)**

Condensing Temperature	Evaporating Temperature (°C)							
	-15	-10	-5	0	5	7.2	10	12
35.0	6.8	6.7	6.7	6.8	6.9	6.9	7.0	7.1
40.0	7.6	7.5	7.5	7.5	7.6	7.6	7.7	7.7
45.0	8.5	8.4	8.3	8.3	8.3	8.4	8.4	8.4
50.0	9.6	9.4	9.3	9.2	9.2	9.2	9.2	9.3
54.4		10.4	10.2	10.1	10.0	10.0	10.0	10.0
60.0			11.5	11.3	11.2	11.1	11.1	11.1
65.0				12.5	12.3	12.2	12.2	12.1

**NOTE:**

\* The performance values subject to change without notice.