

## RATED PERFORMANCE

|  |                     |   |                        |
|--|---------------------|---|------------------------|
|  |                     |   | 220-2240 V             |
| CAPACITY                               | W                   | ☆ | <b>3580/3615 ± 5%</b>  |
| MOTOR INPUT                            | W                   | ☆ | <b>1240/1330 ± 5%</b>  |
| CURRENT                                | A                   | ☆ | <b>5.82 /6.10 ± 5%</b> |
| COP                                    | W/W %               | ☆ | <b>289/272 ± 5%</b>    |
| SOUND LEVEL dB(A)<br>SOUND POWER LEVEL | dB (A)<br>(A RANGE) | ★ | <b>68</b><br>MAX       |
| VIBRATION                              | m/s <sup>2</sup>    | ★ | <b>3.3</b><br>MAX      |

## ☆ RATING CONDITIONS

- RATED VOLTAGE : 1 φ -50HZ-220/240V
- COND. TEMP. : 54.4℃
- EVAP. TEMP : 7.2℃
- RETURN GAS TEMP : 35℃
- LIQUID TEMP. : 46.1 ℃
- AMBIENT TEMP. : 35℃
- FORCED AIR

ACCORDING TO TOSHIBA' S CALORIEMETER STANDARD