

## STANDARD OF PERFORMANCE

## RATED PERFORMANCE

|                                                  |                  |                         | 220-240 V |
|--------------------------------------------------|------------------|-------------------------|-----------|
| CAPACITY                                         | W                | ☆ <b>4310/4355</b> ± 5% |           |
| MOTOR INPUT                                      | W                | ☆ <b>1370/1405</b> ± 5% |           |
| CURRENT                                          | A                | ☆ <b>6.3/6.1</b> ± 5%   |           |
| COP                                              | W/W %            | ☆ <b>315/310</b> ± 5%   |           |
| SOUND LEVEL dB(A) (A RANGE)<br>SOUND POWER LEVEL | dB(A)            | ★ <b>67</b><br>MAX      |           |
| VIBRATION                                        | m/s <sup>2</sup> | ★ <b>3.3</b><br>MAX     |           |

## ☆ RATING CONDITIONS

- RATED VOLTAGE : 1φ-50Hz-220/240V
- COND. TEMP. : 54.4℃
- EVAP. TEMP : 7.2℃
- RETURN GAS TEMP : 35℃
- LIQUID TEMP. : 46.1℃
- AMBIENT TEMP. : 35℃
- FORCED AIR
- 

ACCORDING TO GMCC'S CALORIEMETER STANDARD