

Invotech Selection Software

REFRIGERANT

R407C

Operation Conditions

Evaporating Temperature(ℓ):	7,2
Condensing Temperature(ℓ):	54,4
Liquid subcooling:	8,3
Suction Superheat:	11,1

Required Capacity(Kw): 0,01

Compressor Selected: YH400T1-105

PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW)	39,09
Power Input (KW)	12,1
COP	3,23
Current (A)	21,5

CPMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm)	248/272/556.7
Weight (kg)	57
Stub Suction (inch)	1 1/8
Stub Discharge (inch)	7/8
Base mounting (hole dia)	190.5X190.5(8.5)
Oil type	POE
Initial charge of oil quantity (L)	3.7
Recharge of oil quantity (L)	3.45
High Side PS Max., (MPa)	3.2
Low Side PS Max., (MPa)	2.0
Displacement(m³/h)	36.5

COMPRESSOR ELECTRICAL DATA

Electricity	380V/50Hz/3P
Standard Conditions	7.2/54.4/11.1/8.3
Normal Power (HP)	13
Normal Capacity (ℓ)	39100
Normal Power input(ℓ)	12100
Normal COP(ℓ/ℓ)	3.23
Normal Current(ℓ)	21.5
Locked Rotor Current(ℓ)	148.5
Maximum operating current(ℓ)	32.2

Model: YH400T1-105

Refrigerant: R407C

Suction Superheat: 11,1

Liquid subcooling: 8,3

Capacity(KW)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	16,17	19,56	23,47	27,97	33,1	38,95	45,58			
30	15,28	18,61	22,45	26,86	31,92	37,68	44,21			
35	14,46	17,71	21,46	25,78	30,73	36,38	42,79	50,03	53,98	
40	13,71	16,85	20,49	24,68	29,51	35,03	41,3	48,39	52,26	
45		15,99	19,49	23,55	28,23	33,59	39,7	46,62	50,41	
50			18,46	22,35	26,86	32,04	37,97	44,7	48,39	
55				21,06	25,38	30,36	36,08	42,6	46,18	
60					23,75	28,51	34	40,29	43,75	
65						26,47	31,71	37,74	41,06	

Power Input(KW)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	5,23	5,32	5,37	5,4	5,43	5,47	5,53			
30	6,43	6,56	6,64	6,69	6,72	6,76	6,81			
35	7,44	7,61	7,73	7,81	7,86	7,91	7,96	8,04	8,09	
40	8,32	8,54	8,7	8,82	8,89	8,96	9,02	9,09	9,14	
45		9,4	9,61	9,77	9,88	9,96	10,04	10,12	10,17	
50			10,51	10,71	10,86	10,98	11,08	11,17	11,22	
55				11,71	11,91	12,06	12,19	12,3	12,36	
60					13,06	13,26	13,43	13,57	13,64	
65						14,63	14,84	15,02	15,1	

Model: YH400T1-105

Refrigerant: R407C

Suction Superheat: 11,1

Liquid
subcooling: 8,3**Current(A)**

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	13,35	13,7	13,94	14,11	14,24	14,34	14,46			
30	14,15	14,5	14,75	14,92	15,05	15,16	15,28			
35	15,08	15,43	15,67	15,84	15,97	16,08	16,2	16,36	16,46	
40	16,18	16,52	16,76	16,93	17,05	17,15	17,26	17,4	17,5	
45		17,83	18,06	18,21	18,31	18,4	18,5	18,63	18,72	
50			19,6	19,73	19,82	19,88	19,96	20,07	20,15	
55				21,54	21,6	21,64	21,69	21,77	21,84	
60					23,71	23,72	23,73	23,78	23,83	
65						26,15	26,12	26,13	26,16	

Mass Flow(Kg/h)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	261,85	339,23	424,52	519,45	625,75	745,13	879,33			
30	256,18	333,86	419,51	514,85	621,61	741,51	876,28			
35	250,64	328,36	414,11	509,62	616,59	736,76	871,85	1023,59	1106,23	
40	245,07	322,59	408,19	503,6	610,54	730,73	865,89	1017,76	1100,49	
45		316,39	401,6	496,66	603,31	723,27	858,25	1009,99	1092,69	
50			394,17	488,64	594,75	714,22	848,78	1000,15	1082,68	
55				479,39	584,71	703,45	837,33	988,07	1070,31	
60					573,04	690,79	823,74	973,61	1055,43	
65						676,11	807,88	956,62	1037,9	