

Invotech Selection Software

REFRIGERANT R410A

Operation Conditions

Evaporating Temperature(ℓ): 7,2
 Condensing Temperature(ℓ): 54,4
 Liquid subcooling: 8,3
 Suction Superheat: 11,1

Required Capacity(Kw): 0,01

Compressor Selected: YH720C1-100

PERFORMANCE AT SPECIFIED OPERATING POINT

Capacity (KW)	72,39
Power Input (KW)	21,96
COP	3,3
Current (A)	38,13

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Length/Width/Height (mm)	356.3/326.2/671.2
Weight (kg)	104
Stub Suction (inch)	1 5/8
Stub Discharge (inch)	1 1/8
Base mounting (hole dia)	232X232(11)
Oil type	POE
Initial charge of oil quantity (L)	5.5
Recharge of oil quantity (L)	5.3
High Side PS Max., (MPa)	4.3
Low Side PS Max., (MPa)	2.0
Displacement(m ³ /h)	46.8

COMPRESSOR ELECTRICAL DATA

Electricity	380V/50Hz/3P
Standard Conditions	7.2/54.4/11.1/8.3
Normal Power (HP)	25
Normal Capacity (ℓ)	71200
Normal Power input(ℓ)	21254
Normal COP(ℓ/ℓ)	3.35
Normal Current(ℓ)	38.5
Locked Rotor Current(ℓ)	266
Maximum operating current(ℓ)	53

Model: YH720C1-100

Refrigerant: R410A

Suction Superheat: 11,1

Liquid subcooling: 8,3

Capacity(KW)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	38,29	44,2	51,65	60,98	72,53	86,64	103,63			
30	31,94	37,79	44,95	53,78	64,61	77,77	93,6			
35	27,63	33,48	40,44	48,83	59,01	71,29	86,04	103,57	113,48	
40	24,64	30,57	37,38	45,42	55,01	66,51	80,23	96,52	105,74	
45		28,35	35,09	42,84	51,93	62,69	75,47	90,6	99,15	
50			32,85	40,38	49,03	59,14	71,05	85,08	93,01	
55				37,33	45,62	55,15	66,26	79,27	86,6	
60					40,99	50,01	60,38	72,45	79,22	
65						43	52,72	63,91	70,16	

Power Input(KW)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5	
25	10,58	11	11,47	12,03	12,68	13,44	14,34			
30	12,01	12,32	12,66	13,05	13,52	14,06	14,71			
35	13,51	13,76	14,02	14,31	14,63	15,01	15,46	16,01	16,32	
40	15,08	15,33	15,55	15,78	16,01	16,28	16,59	16,96	17,18	
45		17	17,25	17,47	17,67	17,87	18,09	18,34	18,49	
50			19,11	19,37	19,58	19,77	19,95	20,14	20,24	
55				21,48	21,76	21,99	22,18	22,34	22,42	
60					24,19	24,51	24,76	24,96	25,05	
65						27,34	27,7	27,99	28,1	

Model: YH720C1-100
 Suction Superheat: 11,1

Refrigerant: R410A
 Liquid subcooling: 8,3

Current(A)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5
25	24,79	25,07	25,29	25,45	25,55	25,62	25,65		
30	26,28	26,54	26,73	26,86	26,95	27	27,02		
35	28,03	28,25	28,41	28,52	28,59	28,62	28,63	28,62	28,61
40	30,08	30,26	30,39	30,48	30,52	30,54	30,53	30,51	30,5
45		32,64	32,74	32,79	32,81	32,8	32,78	32,75	32,73
50			35,49	35,52	35,51	35,48	35,44	35,39	35,37
55				38,71	38,67	38,62	38,56	38,5	38,47
60					42,36	42,28	42,2	42,12	42,08
65						46,52	46,41	46,31	46,26

Mass Flow(Kg/h)

Tc\Te	-25	-20	-15	-10	-5	0	5	10	12,5
25	570,8	685,96	819,76	972,84	1145,85	1339,44	1554,26		
30	559,2	673,45	807,76	962,78	1139,16	1337,54	1558,57		
35	544,41	656,88	790,84	946,93	1125,8	1328,1	1554,47	1805,57	1940,59
40	527,21	637,03	769,76	926,05	1106,55	1311,89	1542,74	1799,73	1938,23
45		614,66	745,3	900,92	1082,17	1289,69	1524,14	1786,15	1927,7
50			718,21	872,29	1053,43	1262,26	1499,44	1765,61	1909,78
55				840,96	1021,1	1230,38	1469,42	1738,88	1885,22
60					985,97	1194,81	1434,84	1706,72	1854,8
65						1156,33	1396,49	1669,91	1819,3